



For more
Information



Please Scan
the QR code

BHARAT BIKER 20W40 (SST)

Bharat Biker 4T Plus+ Semi Synthetic oil is a blend of Mineral and Synthetic base Stock and Blend of Selective high-performance Additives, which protects Engine, Transmission and wet clutch of new generation 4-Stroke two wheelers. Bharat Biker 4T Plus+ comes in 4 Types of SAE rating i.e., 10W30, 20W40, 20W50, 15W50 with respectively performance levels are exceeds API SN, API SM and the stringent specifications of JASO MA2 for 4 Stroke two wheelers.



Application:

Bharat Biker 4T Plus+ is suitable for all modern 4 stroke motorcycle engines which comes under cylindrical capacity 100 to 500. where API SN (and below) and JASO MA2 and MA specifications are recommended.

- Latest generation high performance Motorcycles and Scooters.
- Suitable for earlier models of Motorcycles and Scooters.

Performance Benefits:

It provides enhanced protection against oxidation and, wear, thereby ensuring smoother performance, cleaner engine and longer engine & oil life.

- Excellent wear protection.
- Longer drain interval.
- Lower clutch slippage.
- Resource Conserving Technology
- Better fuel economy.

Recommendation:

Bharat Biker 20W40 (SST) 4 stroke bike engine oil can be use Above 125 CC engine bikes.

Typical Data Specifications:

SR. NO.	CHARACTERISTICS	TEST	UNIT	RANGE	
1	SAE Rating	-	-	20W40	20W40
2	Performance Level	-	-	API SM	API SN
3	Appearance	VISUAL	-	C & B	C & B
4	Kinematic Viscosity @ 40°C cSt	ASTM D445	mm ² /s	120	124
5	Kinematic Viscosity @ 100°C cSt	ASTM D445	mm ² /s	14	14
6	Viscosity Index min.	ASTM D2270	none	110	120
7	Flash Point COC °C	ASTM D92	°C	215°C	217°C
8	Pour Point °C max.	ASTM D97	°C	-25°C	-27°C
9	TBN min.	ASTM D2896	mgKOH/g	8	9
10	Density, @ 15°V	-	-	0.880	0.880

***The specifications are subject to variations/development/customization.**

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Available Packing Sizes: 900ml, 1 ltr, 50 ltrs, 55 ltrs, 210 ltrs.

Health & Safety: based on available information, this product is not expected to produce any adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the internet. This product should not be used for purposes other than its intended use, if disposing of used product, take care to protect the environment.