



For more
Information



Please Scan
the QR code

BHARAT CNG 20W50

Bharat CNG 20W50 is specifically formulated with a multi-protection formula to deliver top-notch protection for engines running on both petrol and CNG fuel. Dual fuel engines, especially those operating on CNG, require extra safeguarding, particularly at high temperatures. To address this need, Bharat CNG 20W50 is fortified with "Radical Busters," which provide oxidation protection specifically tailored for CNG applications. Additionally, this advanced formula includes special anti-wear agents that offer superior protection against wear and tear, ultimately extending the life of your engine. With Bharat CNG 20W50, you can trust that your engine is well-protected and can continue to perform optimally for longer durations.



Application:

Bharat CNG 20W50 Engine Oil is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends 20W50 CNG Engine Oil.

Performance Benefits:

During its working life, your engine faces challenges from combustion by-products that can form deposits, and thicken the oil. Bharat CNG 20W50 helps combat these issues in two ways:

- Offers oxidation protection at high operating temperatures to safeguard engine integrity.
- Provides comprehensive wear protection across high and low temperature ranges.
- Engineered to prevent the accumulation of sludge, maintaining engine cleanliness and efficiency.
- Helps in regulating engine temperature, ensuring optimal performance and longevity.

Typical Data Specifications:

SR. NO.	CHARACTERISTICS	TEST	UNIT	RANGE
1	SAE Rating	-	-	20w50
2	Performance Level	-	-	API SM
3	Appearance	VISUAL	-	C & B
4	Kinematic Viscosity @ 40°C cSt	ASTM D445	mm ² /s	149
5	Kinematic Viscosity @ 100°C cSt	ASTM D445	mm ² /s	17.4
6	Viscosity Index min.	ASTM D2270	none	128
7	Flash Point COC °C	ASTM D92	°C	215°C
8	Pour Point °C max.	ASTM D97	°C	-27°C

***The specifications are subject to variations/development/customization.**

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Available Packing Sizes: 1 ltr, 3 ltr, 3.5 ltr, 5ltrs, 7 ltr, 7.5 ltr, 10 ltrs, 26 ltr, 50 ltr, 55 ltrs, 210 ltrs.

Health & Safety: based on available information, this product is not expected to produce any adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the internet. This product should not be used for purposes other than its intended use, if disposing of used product, take care to protect the environment.